





Specifications (PowerShot ELPH 160 / IXUS 160)

Last Updated : 12-Dec-2014

Issue Number : **6200246200**

Image Sensor	Max. Camera Effective Pixels	Approx. 20.0 megapixels
Lens	Focal Length	5.0 (W) – 40.0 (T) mm (35mm film equivalent: 28 (W) – 224 (T) mm)
	Zoom magnification	8x zoom
	Focusing Range	AUTO : 1 cm (0.4 in.) – infinity (W) / 1.3 m (4.3 ft.) – infinity (T) Other modes  5 cm (2.0 in.) – infinity (W) / 1.3 m (4.3 ft.) – infinity (T)  * 1 – 50 cm (0.4 in. – 1.6 ft.) (W) / -  * 3.0 m (9.8 ft.) – infinity (W) / 3.0 m (9.8 ft.) – infinity (T) * Not available in some shooting modes.
Digital Zoom		Digital Zoom Mgnification: approx 4x Maximum magnification with the optical zoom: 32x
Imaging Processor		DIGIC 4+
LCD Monitor	Type	Color TFT LCD
	Size	2.7-type
	Effective Pixels	Approx. 230,000 dots
	Aspect Ratio	4:3
Focus	Control System	TTL autofocus
Metering System		Evaluative, Center-weighted average, Spot
Exposure Compensation (Still images) / Exposure Shift (Movies)		Available range (stops) in 1/3 stop increments ±2
ISO Speed (Standard Output Sensitivity, Recommended Exposure Index)	ISO Auto Range (Auto mode)	AUTO 100 - 1600
	Stop Increments	1-stop increments
White Balance		Auto, Day Light, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
Shutter Speed		AUTO mode, automatically set range: 1 – 1/2000 sec.
Aperture	Type	Circular Diaphragm
	f/number	f/3.2 / f/9.0 (W), f/6.9 / f/20 (T)
Flash	Modes	Auto, On, Slow Synchro, Off
	Range	50 cm – 3.0 m (W), 1.3 – 1.5 m (T)
Shooting Modes		Auto, P, Live View Control, Digital IS, Portrait, Face Self-timer, Low Light, Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Snow, Fireworks, Long Shutter
Continuous Shooting	Speed	AUTO, P : Approx. 0.8 shots/sec.
		 Low light: Approx. 2.2 shots/sec.
Number of Shots(Based on CIPA Guidelines)		Approx. 220 Eco Mode On: Approx. 300
Recording Media		SD Memory card / SDHC Memory card / SDXC Memory card
File Format		Design rule for Camera File system, DPOF (version 1.1) compliant
	Still Images	Exif 2.3 (JPEG)

Data Type	Movies	MOV (Video: H.264/MPEG-4 AVC; Audio: Linear PCM (monaural))
Recording Pixels	Still Images	L (Large): 20M/5152x3864 M1 (Medium 1): 10M/3648x2736 M2 (Medium 2): 3M/2048x1536 S (Small): 0.3M/640x480 W (Widescreen): 5152x2896
	Movies	HD : 1280 x 720 VGA : 640 x 480
Interface		Hi-speed USB Analog audio output (monaural) Analog video output (NTSC/PAL)
Direct Print Standard		PictBridge
Power Source		Battery Pack NB-11LH/NB-11L AC Adapter Kit ACK-DC90
Operating Temperature		0 - 40 °C
Operating Humidity		10 - 90 %
Dimensions (Based on CIPA Guidelines)		95.2 x 54.3 x 22.1 mm (3.75 x 2.14 x 0.87 in.)
Weight (Based on CIPA Guidelines)		Approx. 127 g (approx. 4.48 oz.; including the battery pack and memory card) Approx. 111 g (approx. 3.92 oz.; camera body only)

(W): Wide angle (T): Telephoto

remarks

- All data is based on tests by Canon.
- Camera specifications or appearance are subject to change without notice.

"Was this helpful?"

- ☐ YES. It solved my issue
☐ It covered my problem, but the solution still didn't work for me
☐ The information on the page is hard to understand
☐ It has nothing to do with my issue

Submit

Click [here](#) to go back.

[Home](#) | [Mobile Version](#) | [Canon Global](#)

[Products](#) | [Business](#) | [Services](#) | [Club](#) | [Shop](#) | [About Canon](#) | [Jobs](#) | [Contact Us](#)

[Terms of Use of Website](#) | [Privacy Policy](#) | [Terms of Purchase](#)

[Terms and Conditions of Use of Club Canon Website](#) | [Club Canon Scheme](#)

All copyrights reserved. Canon Hongkong Company Limited.